

Erratum: “Toward efficient and tailorable mid-infrared emitters utilizing multilayer graphene” [Appl. Phys. Lett. 120, 051105 (2022)]

Cite as: Appl. Phys. Lett. 120, 089901 (2022); <https://doi.org/10.1063/5.0087361>

Submitted: 04 February 2022 • Accepted: 07 February 2022 • Published Online: 22 February 2022

Prarthana Gowda,  Dean A. Patient, Simon A. R. Horsley, et al.



View Online



Export Citation



CrossMark

ARTICLES YOU MAY BE INTERESTED IN

Tunnel magnetodielectric effect: Theory and experiment

Applied Physics Letters 120, 082901 (2022); <https://doi.org/10.1063/5.0077879>

Broadband, efficient extraction of quantum light by a photonic device comprised of a metallic nano-ring and a gold back reflector

Applied Physics Letters 120, 081103 (2022); <https://doi.org/10.1063/5.0082347>

Reducing solid conduction in electrothermally driven MEMS Pirani gauge using integrated polymeric thin film

Applied Physics Letters 120, 084101 (2022); <https://doi.org/10.1063/5.0079857>

 QBLOX



1 qubit

Shorten Setup Time

Auto-Calibration

More Qubits

Fully-integrated

Quantum Control Stacks

Ultrastable DC to 18.5 GHz

Synchronized <<1 ns

Ultralow noise



100s qubits

[visit our website >](#)

Erratum: “Toward efficient and tailorable mid-infrared emitters utilizing multilayer graphene” [Appl. Phys. Lett. 120, 051105 (2022)]

Cite as: Appl. Phys. Lett. **120**, 089901 (2022); doi: [10.1063/5.0087361](https://doi.org/10.1063/5.0087361)

Submitted: 4 February 2022 · Accepted: 7 February 2022 ·

Published Online: 22 February 2022



View Online



Export Citation



CrossMark

Prarthana Gowda, Dean A. Patient, Simon A. R. Horsley, and Geoffrey R. Nash^{a)}

AFFILIATIONS

College of Engineering, Mathematics and Physical Sciences, University of Exeter, Exeter EX4 4QF, United Kingdom

^{a)}Author to whom correspondence should be addressed: g.r.nash@exeter.ac.uk

<https://doi.org/10.1063/5.0087361>

The authors would like to correct an error in the original version of the published article.¹ In the published article, the $(\omega_0^2 - \omega^2)$ terms in the denominator of Eq. (6), which gives the expression for the permittivity, did not appear as being squared. The correct expression for the permittivity is

$$\epsilon(\omega) = 1 + \frac{A(\omega_0^2 - \omega^2)}{(\omega_0^2 - \omega^2)^2 + (\gamma\omega)^2} + i \frac{A\gamma\omega}{(\omega_0^2 - \omega^2)^2 + (\gamma\omega)^2}.$$

The data plotted in Fig. 4 were calculated using the correct expression for the permittivity, and thus, the conclusions of the paper are not affected by this error.

¹P. Gowda, D. A. Patient, S. A. R. Horsley, and G. R. Nash, *Appl. Phys. Lett.* **120**, 051105 (2022).