

# Geology

## Hydrodynamic controls on alluvial ridge construction and avulsion likelihood in meandering river floodplains

--Manuscript Draft--

<b>Manuscript Number:</b>	G40104R1
<b>Full Title:</b>	Hydrodynamic controls on alluvial ridge construction and avulsion likelihood in meandering river floodplains
<b>Short Title:</b>	Hydrodynamic controls on alluvial ridge construction and avulsion likelihood
<b>Article Type:</b>	Article
<b>Keywords:</b>	Hydrodynamic; avulsion; floodplain; alluvial ridge
<b>Corresponding Author:</b>	Andrew Nicholas University of Exeter Exeter, Devon UNITED KINGDOM
<b>Corresponding Author Secondary Information:</b>	
<b>Corresponding Author's Institution:</b>	University of Exeter
<b>Corresponding Author's Secondary Institution:</b>	
<b>First Author:</b>	Andrew Nicholas
<b>First Author Secondary Information:</b>	
<b>Order of Authors:</b>	Andrew Nicholas Rolf Aalto Greg Sambrook Smith Arved Schwendel
<b>Order of Authors Secondary Information:</b>	
<b>Manuscript Region of Origin:</b>	
<b>Abstract:</b>	<p>Existing models of alluvial stratigraphy often neglect the hydrodynamic controls on channel belt and floodplain sedimentation, and predict avulsion using topographic metrics, such as channel belt super-elevation. This study provides a first demonstration of the potential for simulating long-term river floodplain evolution (over &gt;500 floods) using a process-based hydrodynamic model. Simulations consider alluvial ridge construction during the period leading up to an avulsion, and assess the controls on avulsion likelihood. Results illustrate that the balance between within-channel and overbank sedimentation exerts a key control on both super-elevation ratios and on the conveyance of water and sediment to the floodplain. Rapid overbank sedimentation creates high alluvial ridges with deep channels, leading to lower apparent super-elevation (the ratio of ridge height to channel depth), and implying reduced avulsion likelihood. However, channel deepening also drives a reduction in channel belt-floodplain connectivity, so that conveyance of water to the distal floodplain is concentrated in a declining number of channel breaches, which may favor avulsion. These results suggest that while super-elevation ratios in excess of a threshold value may be a necessary condition for a meandering river avulsion, avulsion likelihood may not be greatest where the super-elevation ratio is maximised. Instead, optimal conditions for avulsion may depend on channel-floodplain hydrodynamic connectivity, determined by the balance between coarse (channel bed forming) and fine (floodplain constructing) sediment delivery. These results highlight a need to rethink the representation of avulsion in existing models of alluvial architecture.</p>

Publisher: GSA  
Journal: GEOL: Geology  
DOI:10.1130/G40104.1

1 Hydrodynamic controls on alluvial ridge construction and  
2 avulsion likelihood in meandering river floodplains

3 **A.P. Nicholas<sup>1</sup>, R.E. Aalto<sup>1</sup>, G.H. Sambrook Smith<sup>2</sup>, and A.C. Schwendel<sup>3</sup>**

4 *<sup>1</sup>Geography, College of Life and Environmental Sciences, University of Exeter, Exeter,*  
5 *EX4 4RJ, UK*

6 *<sup>2</sup>School of Geography, Earth and Environmental Sciences, University of Birmingham,*  
7 *Birmingham, B15 2TT, UK*

8 *<sup>3</sup>School of Humanities, Religion & Philosophy, York St John University, York, YO31*  
9 *7EX, UK*

10 **ABSTRACT**

11 Existing models of alluvial stratigraphy often neglect the hydrodynamic controls  
12 on channel belt and floodplain sedimentation, and predict avulsion using topographic  
13 metrics, such as channel belt super-elevation. This study provides a first demonstration of  
14 the potential for simulating long-term river floodplain evolution (over >500 floods) using  
15 a process-based hydrodynamic model. Simulations consider alluvial ridge construction  
16 during the period leading up to an avulsion, and assess the controls on avulsion  
17 likelihood. Results illustrate that the balance between within-channel and overbank  
18 sedimentation exerts a key control on both super-elevation ratios and on the conveyance  
19 of water and sediment to the floodplain. Rapid overbank sedimentation creates high  
20 alluvial ridges with deep channels, leading to lower apparent super-elevation (the ratio of  
21 ridge height to channel depth), and implying reduced avulsion likelihood. However,  
22 channel deepening also drives a reduction in channel belt-floodplain connectivity, so that

23 conveyance of water to the distal floodplain is concentrated in a declining number of  
24 channel breaches, which may favor avulsion. These results suggest that while super-  
25 elevation ratios in excess of a threshold value may be a necessary condition for a  
26 meandering river avulsion, avulsion likelihood may not be greatest where the super-  
27 elevation ratio is maximised. Instead, optimal conditions for avulsion may depend on  
28 channel-floodplain hydrodynamic connectivity, determined by the balance between  
29 coarse (channel bed forming) and fine (floodplain constructing) sediment delivery. These  
30 results highlight a need to rethink the representation of avulsion in existing models of  
31 alluvial architecture.

## 32 **INTRODUCTION**

33 River avulsion involves the movement of alluvial channels, generally from areas  
34 of high topography (alluvial ridges) to low points in the fluvial landscape (e.g., distal  
35 flood basins). Such avulsions represent significant hazards with social and economic  
36 consequences (Sinha, 2009). They also exert a key control on the evolution of river and  
37 floodplain morphology (Slingerland and Smith, 2004) and the stratigraphic architecture  
38 of sedimentary basins (Hajek et al., 2010). Multiple factors are known to influence  
39 avulsion likelihood, including valley floor morphology, channel belt aggradation rate,  
40 flood magnitude, floodplain vegetation and the grain size characteristics of the river  
41 sediment load and valley deposits (Hajek and Wolinsky, 2012), yet avulsions remain  
42 difficult to predict. Process-based numerical models have provided important insights  
43 into aspects of avulsion mechanics, including the stability of bifurcation points in braided  
44 river networks (Bolla Pittaluga et al., 2003), delta channel branches (Edmonds and  
45 Slingerland, 2010) and crevasse splay sites where avulsions may occur (Slingerland and

46 Smith, 1998). However, models of long-term fluvial landscape evolution and alluvial  
47 stratigraphy (Mackey and Bridge, 1995; Jerolmack and Paola, 2007; Karssenber and  
48 Bridge, 2008) typically treat avulsion as a stochastic process, or predict avulsion using  
49 simple topographic metrics (e.g., the ratio of the down-valley to cross-valley surface  
50 gradients, or the channel belt super-elevation above the distal floodplain normalized by  
51 the channel depth). Such models tend to neglect or simplify the role of hydrodynamics,  
52 because solution of the governing equations describing fluid flow is computationally  
53 expensive. Herein, we seek to investigate the hydrodynamic controls on floodplain  
54 evolution and alluvial ridge construction in the period prior to an avulsion, and the  
55 implications for the prediction of avulsion likelihood.

## 56 **METHODS**

57 Floodplain evolution was simulated using a new numerical model of flow,  
58 overbank sedimentation and meander migration. The simulations reported here do not  
59 represent specific rivers, but provide insight into the general behavior of large  
60 meandering sand-bed rivers, and the construction of floodplain topography in the period  
61 between avulsions. Details of the modeling approach are provided in the Data Repository.  
62 In summary, the model solves the depth-averaged shallow-water equations and an  
63 advection-diffusion equation representing suspended sediment transport and overbank  
64 deposition for three grain sizes (sand, silt and clay). These equations are solved in the  
65 channel along a series of rectangular cross-sections (using a 1D numerical scheme) and  
66 on a grid of cells representing the floodplain (using a 2D scheme). A sequence of floods  
67 is simulated, each with the same hydrograph of 20 days duration, with peak and  
68 minimum discharges of  $15,000 \text{ m}^3\text{s}^{-1}$  and  $2,500 \text{ m}^3\text{s}^{-1}$ . After each flood, channel

69 migration is simulated using the meander migration model of Howard and Knutson  
70 (1984), which includes neck cutoffs. Channel cross-section bed elevations are then  
71 incremented by a defined rate of bed aggradation ( $A$ ) that is constant for all locations (see  
72 Data Repository). The channel is assumed herein to have a fixed width of 500m (equal to  
73 twice the floodplain grid cell size of 250 m). The channel has a constant slope that is set  
74 by the slope of the floodplain and the channel sinuosity (i.e., channel bed elevations are  
75 not determined by sediment transport calculations). Channel depth is determined by the  
76 difference between the channel bed elevation and the floodplain height in adjacent grid  
77 cells. Initial conditions for each simulation are a planar floodplain with a constant  
78 downstream gradient, and a straight channel with a constant depth. The total sediment  
79 concentration ( $S$ ) at the model inlet is defined as a function of discharge ( $Q$ ) using a  
80 sediment rating curve (Syvitski, et al., 2000):  $S = C Q^{1.5}$ , where  $C$  is constant during each  
81 simulation, such that each flood has a constant sediment load. A set of 31 simulations,  
82 each consisting of 580 floods, were carried out (see Data Repository) to investigate the  
83 effects on floodplain and alluvial ridge construction of changes in bed aggradation rate  
84 ( $A$ ) and suspended sediment load (controlled by varying  $C$ , which is proportional to the  
85 load and depends in nature on the controls on basin erosion rates, such as relief and  
86 climate).

## 87 **RESULTS**

88         During all simulations, channel and floodplain evolution follows a similar  
89 sequence (Fig. 1). The straight initial channel begins to meander and bend amplitude  
90 increases until cutoff occurs. The channel belt widens and the number of abandoned  
91 channel elements increases progressively. Near-channel sedimentation creates levees that

92 are breached by lateral erosion where bend migration is rapid (at bend apices). Levee  
93 breaches promote formation of splay deposits and sediment transport away from river.  
94 Low lying abandoned channels are also sites of preferential sedimentation, and provide  
95 pathways for sediment conveyance to the distal floodplain.

96         Deposition within the channel belt drives construction of an alluvial ridge (Fig. 2).  
97 Progressive growth of the ridge alters inundation patterns so that flow is increasingly  
98 restricted to conveyance paths associated with levee breaches and with low-lying distal  
99 flood basins (Fig. 1C). This tendency is also driven by an increase in channel depth  
100 resulting from sedimentation near the channel, particularly when the rate of channel bed  
101 aggradation is low. There is also a transition in sedimentation styles, from splay  
102 dominated deposition in the early stages of simulations, to infilling of cutoff channels in  
103 the later stages.

104         Overall, floodplain inundation declines over the course of simulations. However,  
105 inundation extent fluctuates between flood events, and significant conveyance of water to  
106 the floodplain continues to occur in the latter stages of most simulations (Fig. 1D).  
107 Fluctuations in inundation are driven by autogenic mechanisms that control channel-  
108 floodplain connectivity (e.g., bend migration, creation and infilling of levee breaches,  
109 bend cutoff) rather than differences in flood magnitude, which does not vary. The  
110 tendency for floodplain inundation to decline is weaker where channel bed aggradation  
111 rates are high (Fig. 1E) and where floodplain sedimentation rates are low (due to low  
112 suspended sediment loads, as in Fig. 1F), both of which lead to lower channel depths.

113         All simulations are characterized by an alluvial ridge with a profile that is  
114 concave in section (Fig. 2). Ridge height is influenced by the channel bed aggradation

115 rate and the suspended sediment load, which set the rate of overbank sedimentation.  
116 Where the balance between bed aggradation and overbank sedimentation promotes an  
117 increase in channel depth, and hence bankfull discharge capacity, ridge height is limited  
118 by a decline in water and sediment delivery to the floodplain. Ridge height is also lower  
119 for finer suspended sediment, for which deposition declines more slowly away from the  
120 river, and for rapid channel migration, which reworks the alluvial ridge.

121 Avulsion likelihood can be related to the channel belt super-elevation ratio ( $\beta$ ),  
122 defined as the height of the alluvial ridge divided by the channel depth (Hajek and  
123 Wolinsky, 2012). Figure 3A shows the relationships between  $\beta$ , the rate of channel bed  
124 aggradation ( $A$ ), and the river suspended sediment load (controlled by  $C$ ). Higher rates of  
125 channel bed aggradation promote greater values of  $\beta$ , which is consistent with existing  
126 understanding (Hajek and Wolinsky, 2012). Higher suspended sediment loads increase  
127 overbank sedimentation, creating higher alluvial ridges and deeper channels, the net  
128 effect of which is to reduce the  $\beta$ . This implies that systems with higher alluvial ridges  
129 and greater rates of floodplain aggradation may be less susceptible to avulsion, due to  
130 increased channel depth and bankfull flow capacity, compared to systems in which the  
131 channel belt aggrades more slowly. Clearly, the balance between in-channel and  
132 overbank sedimentation exerts a key control on  $\beta$ .

133 Most simulations reported here use a suspended sediment load composed of 5%  
134 sand, 75% silt and 20% clay. For simulations with a finer load (comprising 5% sand, 20%  
135 silt and 75% clay), increased sediment conveyance away from the channel leads to lower  
136 channel super-elevation values. For only one such simulation is  $\beta > 1$ , which is commonly  
137 treated as a plausible threshold for avulsion (Jerolmack and Paola, 2007; Hajek and

138 Wolinsky, 2012). Simulations in which bank erodibility was adjusted to be either 50% (or  
139 150%) of the default erodibility value, induced changes in rates of bank migration of  
140 similar magnitude. However, the resulting changes in  $\beta$  were small (a 15% increase in  $\beta$   
141 for less erodible banks and a 6.5% reduction in  $\beta$  for weaker banks). This suggests that  
142 the role of river migration in controlling the creation of flow breach points may be more  
143 significant than its influence on channel super-elevation.

144         One limitation of theory that predicts avulsion likelihood based on topographic  
145 indices is that it does not account for the hydrodynamic controls on channel-floodplain  
146 connectivity. Herein, we calculate a simple metric of floodplain hydrodynamic  
147 connectivity ( $\alpha$ ) that is equal to the mean depth of water on the floodplain after the flood  
148 peak, divided by the fraction of the channel-floodplain interface that is inundated (the  
149 location of this interface is illustrated in Fig. 1E). Figure 3b shows that in general, for a  
150 given rate of channel bed aggradation, higher suspended sediment loads (controlled by  $C$ )  
151 promote greater inter-flood variability in  $\alpha$  and higher peak values of  $\alpha$  as the alluvial  
152 ridge develops. This inter-flood variability in  $\alpha$  is a product of changes in channel-  
153 floodplain connectivity driven by the autogenic mechanisms outlined above. Moreover,  
154 this autogenic signal is stronger in systems with high suspended sediment loads that  
155 promote rapid overbank sedimentation, deep channels and more localized bank  
156 breaching. Figure 3c illustrates values of  $\alpha_{95}$ , the 95<sup>th</sup> percentile of  $\alpha$  values, calculated  
157 over the final 200 floods of each simulation. Peak values of  $\alpha_{95}$  occur where the channel  
158 bed aggradation rate is lowest and the suspended sediment load is highest. Such  
159 conditions maximise channel depth and the delivery of water to the floodplain through  
160 localized bank breaches.



161 **DISCUSSION**

162 Existing models of alluvial stratigraphy often use topographic indices to predict  
163 avulsion likelihood (Mackey and Bridge, 1995; Jerolmack and Paola, 2007; Karszenberg  
164 and Bridge, 2008). Our results suggest that changes in channel depth are a key control on  
165 water and sediment conveyance to the floodplain, hence metrics that do not incorporate  
166 depth (e.g., slope ratios) may be less useful than metrics that do (e.g., super-elevation  
167 ratios). Moreover, the usefulness of super-elevation ratios may depend upon how channel  
168 depths are determined. For example, many models of alluvial stratigraphy estimate  
169 channel depth using hydraulic geometry relations that are under-pinned by the concept of  
170 river equilibrium or have no mechanistic basis (c.f. Paola, 2000). The applicability of  
171 such relations in aggrading (i.e., non-equilibrium) channels is questionable. Channel  
172 depth is more usefully conceptualised as a product of the difference between the rates of  
173 river bed and floodplain aggradation, where the latter reflects the balance between  
174 floodplain lowering due to channel migration (Lauer and Parker, 2008) and the rate of  
175 overbank sedimentation. By adopting such an approach here, albeit with a simplified  
176 representation of channel bed aggradation, we have shown that systems characterized by  
177 high suspended sediment loads that build large alluvial ridges may be characterized by  
178 deep channels and a lower than expected super-elevation ratio. This suggests that  
179 approaches that rely on equilibrium channel theory, or which treat the channel belt as a  
180 single unit that aggrades at a uniform rate, rather than resolving channel and floodplain  
181 aggradation separately, may have limited utility for representing avulsion likelihood.

182 The existence of a positive correlation between channel super-elevation and  
183 avulsion likelihood is a principle that is firmly established in alluvial sedimentology

184 (Hajek and Wolinsky, 2012). Our results show that growth of an alluvial ridge is  
185 associated with changes in water and sediment conveyance to the floodplain that are  
186 controlled by changes in channel depth, and by inter-flood variability in channel-  
187 floodplain connectivity driven by autogenic mechanisms. We hypothesize that avulsion  
188 likelihood will be maximised in systems where water conveyance to the floodplain is  
189 concentrated (e.g., in a small number of breach points), rather than where floodwater is  
190 transferred to the floodplain over a large fraction of the channel belt-floodplain interface,  
191 because concentrated flow will be associated with greater erosion potential. Our results  
192 suggest that the former condition is favored by high suspended sediment loads that build  
193 deep channels and infill some levee breaches so that conveyance to the floodplain is  
194 localized. However, these conditions do not yield the highest super-elevation ratios,  
195 hence interpretation of such metrics as simple indicators of avulsion likelihood is  
196 problematic.

197         We propose that, in low gradient meandering rivers such as those considered here,  
198 conditions for avulsion are optimised where the balance of bedload and suspended load  
199 favors two conditions: (1) sufficient channel bed aggradation to maintain water and  
200 sediment delivery to the floodplain and thus create an alluvial ridge; (2) sufficient  
201 suspended load to allow the construction of deep channels characterized by localized  
202 channel-floodplain connectivity, and focused flow conveyance along potential avulsion  
203 pathways. While super-elevation ratios in excess of a threshold value may be a necessary  
204 condition for a meandering river avulsion, it is not certain that avulsion likelihood will be  
205 greatest where the super-elevation ratio is maximised.

206 Our results do not consider situations in which the rate of channel bed aggradation  
207 greatly exceeds the rate of overbank sedimentation, such that the channel is filled rapidly  
208 and avulsions are frequent. Moreover, our assumption of spatially and temporally  
209 uniform channel aggradation is more applicable in lowland rivers, and is not  
210 representative of environments characterized by episodic and/or localized channel  
211 aggradation (e.g., upland rivers and alluvial fans). Because our model simulations  
212 prescribe the channel bed aggradation rate and assume that the channel width is fixed,  
213 they likely under-estimate the potential for complex behavior resulting from changes in  
214 the ratio of coarse to fine sediment supply. Despite that, these results demonstrate the  
215 potential for investigating the controls on floodplain construction over periods of  
216 centuries to millennia, using a model underpinned by a physics-based treatment of  
217 hydrodynamics (i.e., the shallow water equations). These simulations highlight a need to  
218 rethink existing conceptual models of avulsion likelihood and their implications for the  
219 interpretation of the alluvial record. In the future, application of high resolution (channel-  
220 resolving) 2D morphodynamic models can afford further insight into the controls on  
221 avulsion (e.g., Hajek and Edmonds, 2014). More specifically, our results suggest that  
222 such models may be particularly important tools for understanding how changes in the  
223 ratio of coarse-to-fine sediment supply promote changes in channel morphology (e.g.,  
224 cross-sectional form), local bed aggradation rates, and sediment exchanges with the  
225 floodplain.

## 226 **SUMMARY**

227 This study provides a first demonstration of the potential for simulating alluvial  
228 ridge construction and floodplain evolution using a process-based model under-pinned by

229 the shallow water equations. Simulations illustrate that hydrodynamic conditions that  
230 likely promote avulsion (e.g., water delivery to the floodplain through a restricted number  
231 of channel breach points) are not necessarily associated with conditions that maximize  
232 established proxies for avulsion likelihood (e.g., channel belt super-elevation normalized  
233 by channel depth). These results highlight a need to rethink the representation of avulsion  
234 in models of alluvial architecture and sedimentary basin filling. Specifically, we  
235 hypothesize that the ratio of coarse to fine sediment delivery to rivers exerts a key control  
236 on avulsion frequency that is not accounted for well by existing models. Moreover, our  
237 results suggest that improved representation of avulsion in models of alluvial architecture  
238 necessitates the decoupling of channel bed and channel belt aggradation rates, and further  
239 consideration of the morphodynamic conditions under which channel-floodplain  
240 hydrodynamic connectivity is primed to optimise avulsion likelihood.

#### 241 **ACKNOWLEDGMENTS**

242 This work was funded by UK NERC grants NE/H009108/1 and NE/H007288/1.  
243 Simulations were performed using the University of Exeter Supercomputer. We thank  
244 Renato Almeida, Peter Burgess and Cari Johnson for their thoughtful reviews that helped  
245 us improve the manuscript.

#### 246 **REFERENCES CITED**

247 Bolla Pittaluga, M., Repetto, R., and Tubino, M., 2003, Channel bifurcation in braided  
248 rivers: Equilibrium configurations and stability: *Water Resources Research*, v. 39,  
249 p. 1046, 10.1029/2001WR001112.

- 250 Edmonds, D.A., and Slingerland, R.L., 2010, Significant effect of sediment cohesion on  
251 delta morphology: *Nature Geoscience*, v. 3, p. 105–109,  
252 <https://doi.org/10.1038/ngeo730>.
- 253 Hajek, E.A., and Edmonds, D.A., 2014, Is river avulsion controlled by floodplain  
254 morphodynamics: *Geology*, v. 42, p. 199–202, <https://doi.org/10.1130/G35045.1>.
- 255 Hajek, E.A., and Wolinsky, M.A., 2012, Simplified process modelling of river avulsion  
256 and alluvial architecture: Connecting models and field data: *Sedimentary Geology*,  
257 v. 257–260, p. 1–30, <https://doi.org/10.1016/j.sedgeo.2011.09.005>.
- 258 Hajek, E.A., Heller, P.L., and Sheets, B.A., 2010, Significance of channel-belt clustering  
259 in alluvial basins: *Geology*, v. 38, p. 535–538, <https://doi.org/10.1130/G30783.1>.
- 260 Howard, A.D., and Knutson, T.R., 1984, Sufficient conditions for river meandering: A  
261 simulation approach: *Water Resources Research*, v. 20, p. 1659–1667,  
262 <https://doi.org/10.1029/WR020i011p01659>.
- 263 Jerolmack, D.J., and Paola, C., 2007, Complexity in a cellular model of river avulsion:  
264 *Geomorphology*, v. 91, p. 259–270, <https://doi.org/10.1016/j.geomorph.2007.04.022>.
- 265 Karszenberg, D., and Bridge, J.S., 2008, A three-dimensional numerical model of  
266 sediment transport, erosion and deposition within a network of channel belts,  
267 floodplain and hill slope: Extrinsic and intrinsic controls on floodplain dynamics and  
268 alluvial architecture: *Sedimentology*, v. 55, p. 1717–1745,  
269 <https://doi.org/10.1111/j.1365-3091.2008.00965.x>.
- 270 Lauer, J.W., and Parker, G., 2008, Modeling framework for sediment deposition, storage,  
271 and evacuation in the floodplain of a meandering river: *Theory: Water Resources*  
272 *Research*, v. 44, p. W04425, [10.1029/2006WR005528](https://doi.org/10.1029/2006WR005528).

- 273 Mackey, S.D., and Bridge, J.S., 1995, Three-dimensional model of alluvial stratigraphy;  
274 theory and applications: *Journal of Sedimentary Research, Section B: Stratigraphy*  
275 and *Global Studies*, v. 65, p. 7–31, [https://doi.org/10.1306/D42681D5-2B26-11D7-](https://doi.org/10.1306/D42681D5-2B26-11D7-8648000102C1865D)  
276 [8648000102C1865D](https://doi.org/10.1306/D42681D5-2B26-11D7-8648000102C1865D).
- 277 Paola, C., 2000, Quantitative models of sedimentary basin filling: *Sedimentology*, v. 47,  
278 p. 121–178, <https://doi.org/10.1046/j.1365-3091.2000.00006.x>.
- 279 Sinha, R., 2009, The Great avulsion of Kosi on 18 August 2008: *Current Science*, v. 97,  
280 p. 429–433.
- 281 Slingerland, R.L., and Smith, N.D., 1998, Necessary conditions for a meandering-river  
282 avulsion: *Geology*, v. 26, p. 435–438, [https://doi.org/10.1130/0091-](https://doi.org/10.1130/0091-7613(1998)026<0435:NCFAMR>2.3.CO;2)  
283 [7613\(1998\)026<0435:NCFAMR>2.3.CO;2](https://doi.org/10.1130/0091-7613(1998)026<0435:NCFAMR>2.3.CO;2).
- 284 Slingerland, R.L., and Smith, N.D., 2004, River Avulsions and Their Deposits: *Annual*  
285 *Review of Earth and Planetary Sciences*, v. 32, p. 257–285,  
286 <https://doi.org/10.1146/annurev.earth.32.101802.120201>.
- 287 Syvitski, J.P., Morehead, M.D., Bahr, D.B., and Mulder, T., 2000, Estimating fluvial  
288 sediment transport: The rating parameters: *Water Resources Research*, v. 36,  
289 p. 2747–2760, <https://doi.org/10.1029/2000WR900133>.

290

## 291 **FIGURE CAPTIONS**

292

293 Figure 1. Spatial patterns of simulated deposit thickness for individual floods. Panels A to  
294 D show deposits for four floods in a simulation for which  $C = 0.003$  and  $A = 0 \text{ m flood}^{-1}$ .  
295 Panels E and F show deposits for two other simulations with contrasting values of  $C$  and

296 *A*, but for the same flood shown in panel D. Flow is from left to right. Green indicates  
297 areas with deposit thickness  $<10^{-6}$  m. The main channel cells are shaded black. The  
298 magenta dashed line in panel E denotes the channel-floodplain interface, used in the  
299 calculation of the floodplain hydrodynamic connectivity metric ( $\alpha$ ).

300

301 Figure 2. Floodplain cross-sections at points located midway along the model domain.  
302 Each panel shows results from a single simulation with different values of *A* and *C*.  
303 Results are shown at four points in time, where *T* indicates the number of floods that have  
304 been simulated.

305

306 Figure 3. A: Super-elevation ratio ( $\beta$ ), which equals the height of the alluvial ridge  
307 divided by the mean channel depth, plotted against the prescribed channel bed  
308 aggradation rate (*A*). Each point represents the model results at the end of a single  
309 simulation. The legend indicates the values of *C* used. (F) indicates a fine sediment load  
310 with 5% sand, 20% silt and 75% clay. In all other simulations, the sediment load  
311 comprises 5% sand, 75% silt and 20% clay. (L) indicates bank erodibility that is 50% of  
312 the default value. (H) indicates bank erodibility that is 150% of the default value. Where  
313 (L) or (H) is not specified, simulations use the default erodibility. B: Time series of the  
314 parameter  $\alpha$ , which is equal to the mean depth of floodwater on the floodplain 60% of the  
315 way through the flood, divided by the fraction of the interface between the channel and  
316 floodplain that is inundated (see dashed line in Fig 1E). Results are shown for three  
317 simulations with contrasting values of *C* (*A* = 0.018 m flood<sup>-1</sup> in all cases). *C*: 95<sup>th</sup>  
318 percentile of the values of the parameter  $\alpha$  calculated over the final 200 floods in each

319 simulation, plotted against the prescribed channel bed aggradation rate ( $A$ ). Symbols are  
320 the same as those used in Figure 3A.

321

322 1GSA Data Repository item 2018xxx, xxxxxxxx, is available online at

323 <http://www.geosociety.org/datarepository/2018/> or on request from

324 [editing@geosociety.org](mailto:editing@geosociety.org).







